

LED Downlight *SK-D01*



Product Specification

Input Voltage	: 100-240V/220-240V 50/60H
CRI	: >80 Ra
Beam Angle	: 120°
Dimming	: No
Operator Temp.	: -20°C-50°C
Ingress Protection	: IP 44

Dimension (mm)	Cut Hole	Model	Power	Lumen	CCT
D140*H80	φ120mm	SK-D401-M08W	8W	1050 lm	3000K / 4000K / 5000K / 6000K
D140*H80	φ120mm	SK-D401-M10W	10W	1560 lm	3000K / 4000K / 5000K / 6000K
D140*H80	φ120mm	SK-D401-M12W	12W	1560 lm	3000K / 4000K / 5000K / 6000K
D180*H80	φ150mm	SK-D501-M12W	12W	1560 lm	3000K / 4000K / 5000K / 6000K
D180*H80	φ150mm	SK-D501-M15W	15W	1950 lm	3000K / 4000K / 5000K / 6000K
D190*H80	φ170mm	SK-D601-M15W	15W	1950 lm	3000K / 4000K / 5000K / 6000K
D190*H80	φ170mm	SK-D601-M20W	20W	2600 lm	3000K / 4000K / 5000K / 6000K
D230*H88	φ200mm	SK-D801-M25W	25W	3250 lm	3000K / 4000K / 5000K / 6000K
H230*H88	φ200mm	SK-D801-M30W	30W	3900 lm	3000K / 4000K / 5000K / 6000K

